



# Rhea 2VOL EN 81-20/50

AUTOMATIC LANDING DOOR



# Rhea 2V OL

## AUTOMATIC LANDING DOOR

Our past work on renovation projects has led us to create the RHEA range. It's custom dimensions allow you to improve accessibility, optimise maintenance and servicing operations, and comply with current regulations.

Upgrading becomes easier.




Lintel min  
FF = 110 mm

exists in full facade  
and small facade

Thickness of  
complete door unit  
150 mm

## The door in your pleasure



### New manufacturing process

- **Reduced installation time** is guaranteed as the door is assembled with a single type of screw
- **Only one person** is needed to perform this operation



### Aesthetics guaranteed

- **No trace of spot welding** on the panels
- **The direction of the brush effect on lintel** is the same as that of the uprights

### dimensions of the RHEA 2 panels side opening automatic landing door

	MIN	MAX
Clear opening (CO)	600	1,300
Clear height (CH)	1,900	2,200
Standard lintel height 200 mm	FF = 145 SF= 110	300
Full facade (FF)	Width, opening uprights = CO / 2+50 Width, standard fixed upright = 150 mm Min = 110	
Small facade (SF)	Width, standard uprights = 110 mm Overhanging in shaft = 95 mm	

Pictures for illustration purposes only

Fire resistance certified

**E 120** as per **EN 81-58**

Ideal for **Modernisation**

Ideal for **Residential market**




- E 120 fire resistance certified as per standard EN 81-58
- In compliance with resistance tests as per standard EN 81-20/50
- Standard 200 mm lintel
- Custom uprights and lintel
- Compatible with existing car door or associated with the SLYCMA Jet-s door

### Standard finishes



Primer



Leather grain  
stainless  
steel D42\*




Grain 220  
brushed  
stainless  
steel\*




Linen stainless  
steel\*

### Accessory finishes



RAL colour\*



Square  
stainless  
steel\*



5WL stainless  
steel\*

\*Optional



**SLYCMA Head Office**  
Parc d'activité du  
Dôme  
4 route du Dôme  
69630 Chaponost  
FRANCE  
Tél. : +33 (0)4 78 86 81 00  
Fax : +33 (0)4 78 86 81 08

**SLYCMA Paris**  
34 route de  
Longjumeau  
Bâtiment 21  
91380 Chilly-Mazarin  
FRANCE  
Tél. : +33 (0)1 69 79 32 10  
Fax : +33 (0)1 69 79 32 15

[www.slycma.com](http://www.slycma.com)