

Gaia 2VOC EN 81-20/50

LANDING DOOR RANGE





GOIO 2V OC AUTOMATIC LANDING DOOR

Because you need high levels of performance, silent doors, robust and with a neat aesthetic, we developed the Gaia range. Able to integrate and respond to both configurations of buildings open to the public (schools, offices, hotels, health centers, train stations, theaters ...) than those good lifts, this new range brings you optimized high standing solution with an unmatched level of reliability.



Simplified Commissioning

- Reducing installation time is guaranteed by the simplified assembly of the door.
- Maintenance is facilitated by the availability of components.



Aestheticism guaranteed

- No visible welding points on panels.
- The brushing direction of the lintel is the same as uprights for the most clear openings.

Dimensions for a GAIA automatic landing door 2 panels central opening

panels central opening	MIN	MAX
Clear opening (CO)	600	1,300
Clear height (CH)	1,900	3,000
Standard lintel height	200	200
Small façade (SF)	Standard uprights width = 110 mm Dimensions in shaft = 69 mm	
Full façade (FF)	Bunch post width = PL /2 + 50	

Certified fire resistance E 120 according to EN 81-58

Ideal for **Public Buildings** Ideal for **good lifts**



- In compliance with EN 81-20/50 and EN 81-71 Class 2 tests
- Standard lintel 200 mm
- Compatible with car door kept or with SLYCMA Jet-S.



SLYCMA Head Office Parc d'activité du Dôme 4 route du Dôme 69630 Chaponost FRANCE Tél. : +33 (0)4 78 86 81 00 Fax : +33 (0)4 78 86 81 08

SLYCMA Paris 34 route de Longjumeau Bâtiment 21 91380 Chilly-Mazarin FRANCE Tél. : +33 (0)1 69 79 32 10 Fax : +33 (0)1 69 79 32 15

www.slycma.com