



Gaia 6VOC

EN 81-20/50

LANDING DOOR RANGE



Gaia 6V OC

AUTOMATIC LANDING DOOR

Because you need high levels of performance, silent doors, robust and with a neat aesthetic, we developed the Gaia range.

Able to integrate and respond to both configurations of buildings open to the public (schools, offices, hotels, health centers, train stations, theaters ...) than those good lifts, this new range brings you optimized high standing solution with an unmatched level of reliability.



Door block thickness : 120 mm

The door deeply



Simplified Commissioning

- Reducing installation time is guaranteed by the simplified assembly of the door.
- Maintenance is facilitated by the availability of components.



Aestheticism guaranteed

- No visible welding points on panels.
- The brushing direction of the lintel is the same as uprights for the most clear openings.

Dimensions for a GAIA automatic landing door 6 panels central opening

	MIN	MAX
Clear opening (CO)	1,400	3,000
Clear height (CH)	1,900	3,000
Standard lintel height	200	200
Small façade (SF)	Standard uprights width = 110 mm Dimensions in shaft = 149 mm	
Full façade (FF)	Bunch post width = PL /6 + 75	

Certified fire resistance
E 120 according to **EN 81-58**

Ideal for **Public Buildings**

Ideal for **good lifts**




- In compliance with EN 81-20/50 tests
- Standard lintel 200 mm
- Compatible with car door SLYCMA Roc

Standard finishings




Primer



Leather grain stainless steel D42*



Grain 220 brushed stainless steel*




Linen stainless steel*


Optional finishings



RAL colour*



Square stainless steel*



5WL stainless steel*

*Optional



SLYCMA Head Office
Parc d'activité du Dôme
4 route du Dôme
69630 Chaponost
FRANCE
Tél. : +33 (0)4 78 86 81 00
Fax : +33 (0)4 78 86 81 08

SLYCMA Paris
34 route de Longjumeau
Bâtiment 21
91380 Chilly-Mazarin
FRANCE
Tél. : +33 (0)1 69 79 32 10
Fax : +33 (0)1 69 79 32 15

www.slycma.com