



Rhea 3VOL EN 81-20/50

AUTOMATIC LANDING DOOR



Rhea 3V OL


AUTOMATIC LANDING DOOR

Our past work on renovation projects has led us to create the RHEA range. It's custom dimensions allow you to improve accessibility, optimise maintenance and servicing operations, and comply with current regulations.

Upgrading becomes easier.



The door in your pleasure



New manufacturing process

- **Reduced installation time** is guaranteed as the door is assembled with a single type of screw
- **Only one person** is needed to



Aesthetics guaranteed

- perform this operation
- **No trace of spot welding** on the panels
- **The direction of the brush effect on lintel is the same as that of the uprights**

Dimensions of the RHEA 3 panels side opening automatic landing door

	MIN	MAX
Clear opening (CO)	600	1,100
Clear height (CH)	1,900	2,200
Standard lintel height 200 mm	FF = 110 SF = 110	300
Full facade (FF)	Width, opening upright = CO / 3+35 Width, standard fixed upright = 110	
Small facade (SF)	Width, standard uprights = 110 mm Overhanging in shaft = 135 mm	

Pictures for illustration purposes only

Certifiée de résistance au feu
E 120 selon EN 81-58

Ideal for **Modernisation**

Ideal for **Residential market**




- E 120 fire resistance certified as per standard EN 81 -58
- In compliance with resistance tests as per standard EN 81 - 1/2
- Standard 110 mm lintel
- Custom uprights and lintel
- Compatible with existing car door or associated with the SLYCMA Laser door

Standard finishes



Primer



Leather grain stainless steel D42*




Grain 220 brushed stainless steel*




Linen stainless steel*


Accessory finishes



RAL colour*



Square stainless steel*



5WL stainless steel*

*Optional



SLYCMA Head Office
Parc d'activité du Dôme
4 route du Dôme
69630 Chaponost
FRANCE
Tél. : +33 (0)4 78 86 81 00
Fax : +33 (0)4 78 86 81 08

SLYCMA Paris
34 route de Longjumeau
Bâtiment 21
91380 Chilly-Mazarin
FRANCE
Tél. : +33 (0)1 69 79 32 10
Fax : +33 (0)1 69 79 32 15

www.slycma.com