



Rhea 4VOC

EN 81-20/50

AUTOMATIC LANDING DOOR



Rhea 4V OC


AUTOMATIC LANDING DOOR

Our past work on renovation projects has led us to create the RHEA range. It's custom dimensions allow you to improve accessibility, optimise maintenance and servicing operations, and comply with current regulations.

Upgrading becomes easier.



the door in your pleasure



New manufacturing process

- **Reduced installation time** is guaranteed as the door is assembled with a single type of screw
- **Only one person** is needed to perform this operation



Aesthetics guaranteed

- **No trace of spot welding** on the panels
- **The direction of the brush effect on lintel is the same as that of the uprights**

dimensions of the RHEA 4 panels centre opening automatic landing door

	MIN	MAX
Clear opening (CO)	600	1,100
Clear height (CH)	1,900	2,200
Standard lintel height 200 mm	110	300
Full facade (FF)	Width, standard uprights = CO / 4+35	
Small facade (SF)	Width, standard upright = 110 mm Overhanging in shaft = 95 mm	

Pictures for illustration purposes only

Fire resistance certified

E 120 as per **EN 81-58**

Ideal for **Modernisation**

Ideal for the **Residential market**




- E 120 fire resistance certified as per standard EN 81-58
- In compliance with resistance tests as per standard EN 81-20/50
- Standard 110 mm lintel
- Custom uprights and lintel
- Compatible with the SLYCMA Laser door

Standard finishes




Primer



Leather grain stainless steel D42*



Grain 220 brushed stainless steel*



Linen stainless steel*

Accessory finishes



RAL colour



Square stainless steel*



5WL stainless steel*

*Optional



SLYCMA Head Office
Parc d'activité du Dôme
4 route du Dôme
69630 Chaponost
FRANCE
Tél. : +33 (0)4 78 86 81 00
Fax : +33 (0)4 78 86 81 08

SLYCMA Paris
34 route de Longjumeau
Bâtiment 21
91380 Chilly-Mazarin
FRANCE
Tél. : +33 (0)1 69 79 32 10
Fax : +33 (0)1 69 79 32 15

www.slycma.com